



17th March, 2010

Australian Stock Exchange Limited
20 Bridge Street
Sydney NSW 2000

Dear Sir/Madam

Re: Revised Version of Appendix 1 – Mining starts at Golden Age

Please be advised that Apex wishes to lodge a revised version of Appendix 1 which was attached to today's ASX statement. The only change is to reverse the east and north co-ordinates, which were inadvertently mis-labelled.

The revised table is attached.

Yours faithfully

Mark Ashley
Managing Director

APPENDIX 1 – BURGUNDY DRILL RESULTS

Northing	Easting	RL	Hole_id	DH	TW	grade	from	to	grams x m
10691.3	10171.9	655.7	AWD0333	2.00	0.7	5.2	253.15	255.15	3.8
10730.1	10178.7	659.6	AWD0337	5.75	2.4	5.7	214.4	220.15	13.7
10711.5	10171.5	638.9	AWD0338	0.85	0.3	14.1	241.75	242.6	4.5
10740.4	10178.3	657.5	AWD0341	5.38	2.3	11.3	206.82	212.2	25.9
10744.4	10180.8	678.8	AWD0342	4.55	2.0	5.8	197.45	202	11.3
10752.1	10178.7	637.9	AWD0343	11.87	4.7	4.1	200.73	212.6	19.3
10757.2	10176.4	648.8	AWD0344	16.67	7.1	2.0	191.64	208.31	14.6
10776.0	10184.1	681.2	AWD0345	10.17	5.2	6.8	166.83	177	35.3
10777.5	10178.6	626.2	AWD0346	15.18	6.8	5.6	185.64	200.82	37.7
10793.6	10185.9	686.7	AWD0347	10.55	5.9	11.3	151.65	162.2	66.4
10787.7	10182.1	625.2	AWD0348	11.15	5.0	5.1	179.35	190.5	25.6
10778.0	10188.6	702.9	AWD0388	1.55	0.8	11.5	163.6	165.15	9.3
10801.8	10193.3	728.0	AWD0389	8.00	4.9	9.2	138.9	146.9	45.0
10798.6	10190.0	717.2	AWD0390	7.30	4.3	32.5	143	150.3	138.3
10803.4	10188.1	699.2	AWD0391	7.00	4.1	15.8	142	149	63.8
10840.7	10202.3	719.8	AWD0394	3.05	2.2	14.1	106.6	109.65	30.4

KEY: DW = Down-hole width (metres), TW = estimated true width (metres), AP = Assays Pending
 True widths are estimate based of average dip and dip direction of the 50 lode in this area -82dip to 276deg as per resource wireframe.
 No top cut applied.

Important Notice

This press release is not an offer of securities for sale in the United States. No security of Apex has been registered under the United States Securities Act of 1933, as amended (the "U.S. Securities Act"), and no such security may be offered or sold in the United States absent registration under the U.S. Securities Act and applicable state securities laws or an exemption from registration under the U.S. Securities Act and such laws.

Competent Person's statement

The information in this report that relates to Exploration Results and Mineral Resources is based on information compiled by Mr. Andrew Thompson who is an employee of the company, Mr. Thompson is a Member of the Australasian Institute of Mining and Metallurgy and has sufficient experience of relevance to the styles of mineralisation and the types of deposits under consideration, and to the activities undertaken, to qualify as Competent Persons as defined in the 2004 Edition of the Joint Ore Reserves Committee (JORC) Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves. Mr. Thompson consents to the inclusion in this report of the matters based on information in the form and context in which it appears.

Assay results are obtained from Intertek (formerly known as Genalysis) in Perth. Samples are prepared using single stage pulverization of the entire sample. Gold assays are obtained using either a 30g or 50g lead collection fire assay digest and atomic absorption spectrometry (AAS) analysis techniques or, in the case of reef quartz such as the core of the Golden Age Reef, large volume leachWELL digest and atomic absorption spectrometry (AAS). The LeachWELL technique is a strong accelerated cyanide leach of a 1Kg sample, designed to minimize the analytical variability in samples containing coarse nuggety gold.

Full analytical quality assurance - quality control (QAQC) is achieved using a suite of certified standards, laboratory standards, field duplicates, laboratory duplicates, repeats, blanks and grind size analysis. Assays quoted in announcements may be of a preliminary nature. Assays used in resource estimates have undergone full QAQC.

The spatial location of samples from underground holes is derived using surveyed rig setups and Reflex multi-shot downhole surveys. True widths are calculated using the mean dip and strike of the mineralization from 3D wireframe models and downhole surveys.

Quoted drill intersections are based on situation specific criteria, which include using a lower cutoff of 1g/t or 2g/t gold and acceptable levels of internal dilution.

Mineral Resources have been estimated using standard accepted industry practices. All Resources have been estimated via Block Ordinary Kriging using 2m composite samples. Top cuts have been applied to the composites and are considered appropriate for the nature and style of mineralization in all cases. Directional grade variography was modeled for all zones based on 2m composites. Geological and mineralization modeling has been achieved by 3D modeling of footwall and hangingwall. Grade interpolation (via Block Ordinary Kriging) was then undertaken using a multiple estimation pass strategy.

Mineral Resources are quoted on the basis of a 4.5g/t Au lower cutoff (LCOG) for underground resources. Where quoted, Mineral Resource tonnes and ounces are rounded to appropriate levels of precision, causing minor computational errors.

Mineral Resources are classified on the basis of drillhole spacing, geological continuity and predictability, geostatistical analysis of grade variability, sampling, analytical, spatial and density QAQC criteria and demonstrated amenability of mineralization style to proposed processing methods.